

STRIPWORKS AEROSOL / (MSDS)

PURPOSE: Multi-use gel baseboard stripper. Prepared by safety department. Revised: 08/02/11

US DOT shipping name: Consumer Commodity, ORM-D.

UN Proper shipping name: AEROSOLS, NON FLAMMABLE, nos, (each not exceeding 1L in capacity) 2.2, UN 1950 (No PG)



SECTION 1 SOURCE INFORMATION

Manufactured by: US Formula Technology

1000 McFarland 400 Blvd, Alpharetta, GA 30004 USA

Phone: 770/ 813-0008 or 800/ 728-7972 Fax: 770/ 813-0470

24 Hour Chemical Emergency Phone: Toll Free: 1-800/535-5053

or Collect 1-352/ 323-3500

SECTION 1 INGREDIENTS (1% or more)

MATERIAL	PEL	TLV	CAS No.
water	N/E	N/E	7732-18-5
ethanolamine*	3 ppm	3 ppm	141-43-5
dipropylene glycol methyl ether*	N/E	N/E	34590-94-8
butane*	800 ppm	1900 mg/m ³	106-97-8
propane*	1000 ppm	2500 ppm	74-98-6

* SARA Title III applies N/E=None Established

Contains no ozone-depleting chemicals.

SECTION 2 PHYSICAL DATA

Appearance and odor: aerosol gel, floral scent

Boiling point: -12°F (-24°C)

Vapor density: Air = 1 > 1

Solubility in water: > 80%

Specific gravity: Water = 1 < 1

pH: 12

Pressure in can at 70°F/ 21°C: 70 psig

SECTION 3 FIRE AND EXPLOSION DATA

Flash Point (for propellant): -132°F (-91°C)

Flammable limits: Lower: 1.8% Upper: 9.5%

Extinguishing media: Foam, CO₂, dry media

Special fire fight procedures: Keep containers cool to prevent rupture

Unusual fire hazards: Contents under pressure

Unusual explosion hazards: Aerosol containers may rupture explosively under heat of fire

SECTION 4 REACTIVITY DATA

Stability: Stable

Conditions to avoid: 120°F+ temperatures, agents or actions compromising packaging, acids

Incompatibility: None known

Hazardous decomposition: By-products undetermined

Hazardous polymerization: Will not occur

SECTION 5 SPILL OR LEAK PROCEDURES

Spill response:

Residue slippery.

Prevent foot traffic. Rinse area with water.

Waste disposal:

Dispose of in accordance with Federal, State and Local law.

Aerosol cans, when vented to atmospheric pressure through normal use, pose no disposal risk

SECTION 6 HEALTH HAZARD DATA

Health hazards: harmful to skin and eyes

Carcinogenicity: none

Medical conditions

aggravated by exposure: pre-existing skin and respiratory disorders

ROUTES OF ENTRY AND SIGNS OF EXPOSURE:

Eyes: redness, irritation

Skin: slippery, burning

Inhalation: possible CNS depression, lightheadedness

Ingestion: unlikely

EMERGENCY FIRST AID:

Eyes: Flush with clean water for 15 minutes, lifting lids, see physician immediately

Skin: Wash thoroughly with soap and water, if irritation develops or persists, see physician

Inhalation: Remove to fresh air
Drink 1/2 cup citrus fruit juice, milk or water.

Ingestion: Damage to esophagus exceeds poisoning potential. Avoid vomiting—aspiration hazard. See physician immediately with this data.

SECTION 7— SPECIAL PROTECTION AND HANDLING

No OSHA PEL has been established for this blend of ingredients.

Eye protection: Safety glasses recommended.

Ventilation: General mechanical

Respiratory protection: No OSHA PEL has been established for this ingredient blend

Skin protection: Impervious nitrile rubber gloves. Do not allow containment against skin. Remove all contaminated clothing and shoes immediately, wash and rinse thoroughly before reuse. Wear slip resistant rubber stripper boots with black pad soles when using product on floor. Read and follow all label directions before use.

Storage and handling

Under pressure! Do not store in direct sunlight.

Store in a cool dry place, away from open flame. For industrial use only.

KEEP OUT OF REACH OF CHILDREN.

Disclaimer

Manufacturer cannot anticipate all conditions of use, or performance in all environments. Manufacturer will not accept responsibility for abuse or misuse of the product. The preceding information is believed to be accurate but is not warranted to be so. In case of a chemical emergency call 1-800/ 535-5053 day or night. If 800 service is not available call collect in the USA: 1-352/ 323-3500. To receive the most current safety data call 770/ 813-0008 during regular office hours, 9:00 am - 5:00 pm EST.

PRODUCT DATA SHEET

STRIPWORKS[™]

Multi-Use Gel Baseboard Stripper

One of our best products. Removes years of accumulated floor waxes, polishes and finishes. Water-based formula clings to vertical or textured surfaces such as cove moldings, door jams and kick-plates. May be useful for paint oversprays and even graffiti. Pleasant scent. Softens most coatings within five minutes. Just wipe off with a scrubbing pad or damp mop. Leaves no harmful residues when dry.

Perfect for hard-to-strip areas where scrubbing machines cannot reach. Spray this product around delicate equipment which cannot be bumped by floor scrubbers. Helps to keep floor stripper from flowing under carpeting, partitions, cabinets, walls, counters, gondolas or vending machines.

Hand wand available for more convenient floor-level application.

Caution: Do not puncture or incinerate aerosol containers.

Proper Shipping Name (US DOT):

Consumer Commodity, ORM-D

Proper Shipping Name (International):

AEROSOLS, NON FLAMMABLE, nos, (each not exceeding 1L in capacity) 2.2, UN 1950

Revised: 08/02/11



US Formula Technology
1000 McFarland 400 Blvd.
Alpharetta, GA 30004 USA

USA: 800/ 728-7972
Tel: 770/ 813-0008
Fax: 770/ 813-0470